



## **SIDDHI TRADE ENTERPRISE**

### **POUR POINT DEPRESANT- PPD**

#### **TECHINAL DATA SHEET**

#### **INTRODUCTION**

A Pour Point Depressant for Lubricating Oils.

#### **FORMULATION**

Recommended at: 0.05% to 0.5% by weight or volume

It is recommended for all lubricating oils where pour point reduction is the major objective. The recommended concentrations depend upon the performance desired and the response of the base oils.

#### **TYPICAL INSPECTIONS CHARACTERISTICS**

##### **Physical Characteristics:**

➤ Specific Gravity @ 15.6 C (60 F)	0.92
➤ Pounds per U.S. Gallon @ 60 F	7.4
➤ Pounds per I.M.P. Gallon @ 60 F	8.88
➤ Viscosity, cSt @ 100 C (210 F)	190
➤ Viscosity, cSt @ 40 C	550

## **POUR POINT DEPRESANT- PPD**

### **SPECIFICATION SHEET**

<b>TEST</b>	<b>PROCEDURE</b>	<b>MIN</b>	<b>MAX</b>
<b>1. PRIMARY ANALYSIS</b>			
Specific Gravity @ 15.6° C	GL-GR-1	0.88	
Oil Blend Viscosity @ 100° C., cst	ASTM D 445	60	
Color, ASTM Dilute	ASTM D 1500		5
% Water	ASTM D 95	0.1	
Blot	GL-BL-1A		PASS
Clarity	CLARK CLAR.		PASS
Appearance		Clear	Liquid Viscous
<b>2. SECONDARY ANALYSIS</b>			
Viscosity @ 40° C., cst	ASTM D 445		550
Flash point, ° C., COC	ASTM D 92		150

On behalf of [Siddhi Trade Enterprise](#), we are pleased to have the opportunity to work with you and we look forward to establishing a solid, mutually beneficial business relationship.

**Please feel free to contact us for further details. Assuring you our best services.**

#### **SIDDHI TRADE ENTERPRISE**

Mayuresh Cosmos Society, Office No.1104, Plot No.37, Sector 11, CBD Belapur, Navi Mumbai 400614, India  
Tel: 022-27561092, Fax: 022-27561279 Email: [info@siddhitrade.co.in](mailto:info@siddhitrade.co.in)  
Website: [www.siddhitrade.co.in](http://www.siddhitrade.co.in)

**BRINGING EXCELLENCE TO THE PINNACLE**