



SIDDHI TRADE ENTERPRISE

TECHNICAL DATA SHEET

GEAR OIL (EP) ADDITIVE

Multi-functional Gear Oil Additive Package

Application:

Gear Oil Additive multifunctional gear oil additive is based on sulphur-phosphorus chemistry. It has been developed for formulating both GL-5 automotive hypoid axle lubricants and industrial gear oils.

Recommended Dosage

✓ **Automotive:**

4.1 - 4.4% weight	API GL-5
2.2% weight	API GL-4

✓ **Industrial:**

1.5% weight	USS 224, David Brown S1.53.101 (E) AGMA 9005-D94, and DIN 51517 part 3
0.1 - 1.0% weight	General EP/antiwear control in industrial systems

Features:

- Performance in both automotive and industrial applications
- Cost savings at all treat levels
- Improved inventory control
- Security and confidence from a product in a family of gear oil additives with an extensive history of trouble-free performance worldwide.

Typical Characteristics

- Appearance Clear Yellow liquid
- Phosphorus, %wt. 1.17
- Sulphur, % wt 30 TO 36
- Specific Gravity @ 15.6/15.6 °C 1.082
- Viscosity @ 100 °C, cSt 9.0
- Flash Point, °C, Min 76

CERTIFICATE OF ANALYSIS

<u>TEST</u>	<u>VALUE</u>
Viscosity @40 CST	Between 70 to 100
Base Fluid Used	Mix of Mineral & Ester
Copper Corrosion	1A
Pour Point °C	-6
Foam Test	Pass
Color	2
Clarity	Pass

On behalf of [Siddhi Trade Enterprise](#), we are pleased to have the opportunity to work with you and we look forward to establishing a solid, mutually beneficial business relationship.

Please feel free to contact us for further details. Assuring you our best services.

SIDDHI TRADE ENTERPRISE

Mayuresh Cosmos Society, Office No.1104, Plot No.37, Sector 11, CBD Belapur, Navi Mumbai 400614, India

Tel: 022-27561092, Fax: 022-27561279 Email: info@siddhitrade.co.in

Website: www.siddhitrade.co.in

BRINGING EXCELLENCE TO THE PINNACLE